

SERVICE SADDLES & REPAIR CLAMPS

425/435 SERIES TECK™ REPAIR CLAMPS



425 Series Clamp

Product Example: 425-0350-08
3" x 8" Finger Gasket



435 Series Clamp with Outlet

Product Example: 435-0350-08-A3TC
4" x 8" 3/4" CC Taper Gasket
Conductivity Pad

Nom. O.D.	Pipe Material		Range	Part Number	Width	Options Add T or C	Part Number	Width	Outlet Add from chart	Options Add T or C
4	IPS	4.50	4.30 - 4.70	425-0450-			435-0450-		-	
4			4.40 - 4.80	425-0460-			435-0460-		-	
4	DI / C900 / cast A	4.80	4.60 - 5.00	425-0480-			435-0480-		-	
4			4.75 - 5.15	425-0495-			435-0495-		-	
4	Cast B, C, D	5.00	4.80 - 5.20	425-0500-			435-0500-		-	
4			5.00 - 5.40	425-0520-			435-0520-		-	
6			6.40 - 6.80	425-0660-			435-0660-		-	
6	IPS	6.63	6.43 - 6.83	425-0663-			435-0663-		-	
6	DI / C900 / cast A	6.90	6.70 - 7.10	425-0690-			435-0690-		-	
6			6.80 - 7.20	425-0700-			435-0700-		-	
6			6.86 - 7.25	425-0705-			435-0705-		-	
6	Cast B, C, D	7.10	6.90 - 7.30	425-0710-			435-0710-		-	
6			7.10 - 7.50	425-0730-			435-0730-		-	
8			8.00 - 8.40	425-0820-			435-0820-		-	
8			8.40 - 8.80	425-0860-			435-0860-		-	
8	IPS	8.63	8.43 - 8.83	425-0863-			435-0863-		-	
8	DI / C900 / cast A, B	9.05	8.85 - 9.25	425-0905-			435-0905-		-	
8			8.98 - 9.38	425-0918-			425-0918-		-	
8	Cast C, D	9.30	9.10 - 9.50	425-0930-			435-0930-		-	
8			9.30 - 9.70	425-0950-			435-0950-		-	
10			10.50 - 10.90	425-1070-			435-1070-		-	
10	IPS	10.75	10.55 - 10.95	425-1075-			435-1075-		-	
10	DI / C900 / cast A, B	11.10	10.90 - 11.30	425-1110-			435-1110-		-	
10			11.05 - 11.45	425-1125-			435-1125-		-	
10	Cast C, D	11.40	11.20 - 11.60	425-1140-			435-1140-		-	
10			11.60 - 12.00	425-1180-			435-1180-		-	
10			11.85 - 12.25	425-1205-			435-1205-		-	
12	IPS	12.75	12.55 - 12.95	425-1275-			435-1275-		-	
12	DI / C900 / cast A, B	13.20	13.00 - 13.40	425-1320-			435-1320-		-	
12			13.15 - 13.55	425-1335-			435-1335-		-	
12	Cast C, D	13.50	13.30 - 13.70	425-1350-			435-1350-		-	
12			13.40 - 13.80	425-1360-			435-1360-		-	
12			13.80 - 14.20	425-1400-			435-1400-		-	
12			14.10 - 14.50	425-1430-			435-1430-		-	

Width	
08	8" wide
12	12" wide
16	16" wide
20	20" wide
24	24" wide

Options:	
T	Taper gasket (grid style) (finger gasket is standard)
C	Conductivity pad

Outlet Size:		Type	
		FIP	AWWA
3	3/4"	F	A
4	1"	F	A
5	1 1/4"	F	A
6	1 1/2"	F	A
7	2"	F	A

Different sizes and configurations available, please call for details.
NBR grid gasket certified to Standard NSF 61.